



Network Critical
The Window to your Network™

SmartNA™ 10 Gigabit Aggregating Filtering TAP

Gain Access and Visibility to your 10 Gigabit Links Today!

- 10 Gigabit SR and LR Passive Optical TAP or connect two (2) 10 Gigabit SR or LR SPAN/Mirrored Ports.
- Two (2) 10 Gigabit directional monitoring ports with optional filtering or One (1) Aggregated 10 Gigabit monitoring port with optional filtering.
- Two (2) 1 Gigabit aggregated monitoring ports with optional filtering.

SmartNA™ 10 Gigabit Aggregating Filtering TAP



Models to Choose From:

1. SNA10G-SR
2. SNA10G-LR

*****See Order Info for more Detail.***

SmartNA™ 10 Gigabit Aggregating Filtering TAP

FEATURES

BENEFITS

Fail-safe technology LinkLock	Assures no disruption of network traffic, even if power is lost to the unit
100% real time traffic visibility	Layer 1 and Layer 2 errors are passed through to monitoring tools for more complete results
1 Gigabit monitoring ports	Use 1 Gigabit monitoring tools to analyze your 10 Gigabit links
Packet slicing	Select what you want to see. For example, the first 128 bytes with a recalculated valid CRC
Complete packet inspection	Most comprehensive enterprise filtering solution on the market
Classified traffic and allows individual filtering on each monitoring port	Accurate time-stamping allows accurate results
Time stamp available on all monitoring ports	Completely secure solution
Managed using secure web browser	Monitor performance on-the-fly
Collect one-second internal statistics	Allow you to see your network performance without an additional tool
Built-in and user-defined graphs	Local or remote access allows flexibility
View remotely over web browser	

ORDER INFO

SNA10G-SR:	Smart Network Access 10 Gigabit Filtering TAP, Multi-mode 10 Gigabit-SR, Passive Optical TAP, 50 micron (850 wavelength) with LC Connectors, (4) monitoring ports: (2) copper 10/100/1000 RJ-45 Aggregating Monitoring Ports with Deep Packet Filtering, 1U Chassis with Ethernet Management Port, Supports Web Interface or Command Line Interface
SNA10G-LR:	Smart Network Access 10 Gigabit Filtering TAP, Single-mode 10 Gigabit_LR, Passive Optical TAP, 9 micron (1310 wavelength) with LC connectors, (4) monitoring ports: (2) copper 10/100/1000 RJ-45 Aggregating Monitoring Ports with Deep Packet Filtering, 1U Chassis with Ethernet Management Port, Supports Web Interface or Command Line Interface

TECHNICAL SPECIFICATIONS

Size Dimensions (WxHxD):	15.3 in x 1.7 in x 13.1 in/ 38.9 cm x 4.3cm x 33.2 cm
Weight:	9 lbs/ 4.1 kg
Operating Temperature:	+32 °F to 104 °F/ 0 °C to +40 °C
Operating Relative Humidity:	90% non-condensing
Storage Temperature:	-4 °F to +158 °F/ -20 °C to +70 °C
Power Input:	60 Watts @ 110 - 240VAC, 1.5A

EUROPEAN HEADQUARTERS:

Network Critical Ltd
 East Throp House, 1 Paddock Road,
 Reading, Berkshire, RG4 5BY
 tel: +44 (0) 118 954 3210



AMERICAS OFFICE:

Network Critical NA LLC
 37 Franklin Street, Suite 100
 Buffalo, NY 14202
 tel: +1-716-558-7280
 fax: +1-716-568-8280